GoPal® U24W

The GoPal AMR solution from Robotize sets new standards for versatility, efficiency and safety in automated internal pallet transport



Technical Specifications
GoPal E22 / GoPal E24 / GoPal E24W / GoPal U24W

TECHNICAL SPECIFICATIONS GoPal® U24W

APPLICATION

Autonomous Mobile Robot (AMR) for transporting very high loads (max. 1200 kg // 2645 lbs) on US/UK pallets.

DIMENSIONS

Length x Width x Height 1400 x 1060 x 340 mm // 55.12 x 41.73 x 13.39 in

Mass 242 kg / 534 lbs

PERFORMANCE

Battery time (autonomy) 6-14 hours or up to 20 km* // 12.4 miles*

Maximum speed 2,2 m/s (7,9 km/h) // 7.2 ft/s (4.9 MPH)

Turning radius (from robot center) 1000 mm // 39.4 in

SAFETY

Laser scanners (360° protection)

Mechanical bumper (360° protection)

4 x emergency stop buttons

ADDITIONAL OBSTACLE AVOIDANCE SENSORS

3 x 3D cameras (two front facing and one rear facing)

BATTERY

Type / Voltage LiFePO₄ / 48 V

Charge time 45 minutes (full charge)


Number of charges About 5000

CHARGER INTERFACE

Automatic docking interface (front)

Connector for manually charging (rear)

*depending on load conditions



TECHNICAL SPECIFICATIONS GoPal® U24W

COMMUNICATION

Wi-Fi 802.11ac

ENVIRONMENTAL

Operating temperature -10°C to $+45^{\circ}\text{C}$ // $+14^{\circ}\text{F}$ to $+113^{\circ}\text{F}$

Humidity (max.) 95% (non-condensing)

FLOOR REQUIREMENTS

Slope average (max.) Near-level (2%)

Friction coefficient (min.) 0.60

Edge height (max.) 3 mm // 0.12 in

LOAD

Payload (max.) 1200 kg // 2645 lbs

Length (max.) 1240 mm // 48.82 in (4.06 ft)
Width (max.) 1020 mm // 40.16 in (3.34 ft)
Height (max.) 2400 mm* // 94.50 in* (7.87 ft*)

PALLET TYPES

US or UK pallets.


PALLET CONDITION

Undamaged, original strength maintained

LANE CONDITIONS

Minimum lane width 1400 mm // 55.12 in (4.60 ft)
Recommended lane width 2300 mm // 90.50 in (7.55 ft)
High speed lane width 3000 mm // 118 in (9.84 ft)

*depending on load conditions



robotize

Advanced internal logistics made safe and simple